



Product Information:

MULTITRANS SA 75W-140

HIGH PERFORMANCE FULLY SYNTHETIC GEAR OIL

Description

Multitrans SA 75W-140 is an advanced, fully synthetic gear oil developed for use in heavy duty axles, including Scania units requiring a lubricants with a STO 2:0A qualification.

The product has high load carrying ability and will protect all critical components over a wide range of operating temperatures and workloads. Rapid circulation from cold will ensure essential component protection at start up and promote the potential for fuel economy. Multitrans SA 75W-140 will also provide effective wear, rust and corrosion protection.

The extremely strong synthetic base fluid maintains lubricating film integrity under the toughest shock load conditions demonstrating superior performance over conventional mineral oils.

Features

- Outstanding frictional durability (reducing the potential for vibration)
- Strong EP protection
- High level of thermal and oxidation stability

Applications

Multitrans SA 75W-140 is designed and recommended for use in heavy duty axle / differential applications where any of the performance levels below are specified by the manufacturer.

Performance Level

API GL-5

API MT-1

SAE J2360

Scania STO 1:0 / STO 2:0A

Arvin Meritor 076-M, 076-Q*

Mack GO-J

ZF TE-ML 05B / 07A / 12B / 12L / 12N / 16F / 19C / 21B

MIL-PRF-2015E

Physical Characteristics

Density @ 15.6°C	0.867
Viscosity @ 100°C, cSt.	24.7
Viscosity @ 40°C, cSt.	185.0
Viscosity Index	165
Flash Point (Closed) °C	168
Pour Point, °C	-46

Figures based on average production values.

*meets the requirements

Part No.s: STT025, STT205

(TDS Multitrans SA 75W-140 – 160119 Issue 1)

